



PREHEAT:
PUSH START AND STOP
SWITCHES SIMULTANEOUSLY

ECO NO.	DATE	REV.	REVISION RECORD	INIT.	DR.
4231	1/24	A	D. 47 WAS 47; ADDED GROUND.	CEU	
4574	5/24	B	ADDED (N/O) TO WATER TEMP SWITCH ADDED (N/C) TO OIL PRESS. SWITCH	JEC	
4743	12/5	C	UPDATED WIRING FOR: BAT. CHARGE RECTIFIER, RELAY, CURRENT TRANS. REMOVED FREE 2 RESISTOR, ADDED BREAKER, REL. COIL, CAP. & APC OUTPUT	TSM	
4819	2/1	D	CHANGE IN TITLE: 3.0/3.5 FROM 4.2/3.5	LLM	
4885	2/1	E	ADDED RESISTOR TO BATTERY CHARGER	JCH	
5004	2/1	F	ADDED JUMPER #10 WHITE/GREEN	RM	
5187	2/1	G	UPDATED BATTERY CHARGING CIRCUIT ADD EXHAUST TEMP SWITCH & 35A C.B. ADDED GROUND WIRE TO STARTER.	TSM	
5262	4/15	H	MOVED 35A BREAK FROM NEUTRAL TO LI. ADDED #10 BLK AND #10 BRN WIRES.	TSM	
5451	2/3	J	ADDED 0.10 OHM BALLAST RESISTOR REDRAN REMOTE CONNECTOR UPSIDE DOWN	GA	

TOLERANCES		WESTERBEKE CORPORATION AVON MA. 02322	
UNLESS OTHERWISE SPECIFIED	INCHES	MILLIMETERS	TITLE
	1/16	1.6	WIRING DIAGRAM / SCHEMATIC
	1/32	0.8	3.0KW/3.5KW BCDT
	1/64	0.4	
	1/128	0.2	
DIMENSIONS IN INCHES	SCALE NONE	DATE	PROJ. NO.
UNLESS OTHERWISE SPECIFIED		02/14/01	
		REV.	44163
		REV.	J