



NOTE:
○ REMOTE CONNECTOR PINS

QTY	REV.	DESCRIPTION	BY	CHKD.	DATE
3061	11-2004	D	ADDED JUMPER BETWEEN TB2-6&7; K2-8&6 WAS CONNECTED TO TB2-6.	GA	
561D	9-17-03	D	ADDED 30A FUSE TO BATTERY CHARGER CONNECTION; REROUTE BATTERY CHARGER CONNECTION TO STARTER INSTEAD OF CIRCUIT BREAKER	GA	
5345	6-27-01	B	ADDED 4.0 BCD TO TITLE, 25A WAS 20A.	TSM	
54062	2-14-02	A	ADDED CURRENT TIMER	Y.S.W.	

ECD NO.	DATE	REV.	REVISION RECORD	AUTH.	DR
---------	------	------	-----------------	-------	----

TOLERANCES UNLESS OTHERWISE NOTED	WIRE DIAMETER	WIRE SIZE	WIRING DIAGRAM/SCHEMATIC, 4.0 BCD - 5.0 BCD - SRC ①
	1/16 IN	#18 AWG	
	3/32 IN	#16 AWG	
	1/8 IN	#14 AWG	
	5/32 IN	#12 AWG	

DATE	BY	REVISION RECORD	AUTH.	DR
------	----	-----------------	-------	----

WESTERBEKE CORPORATION
AVON, MA, 02322

WIRING DIAGRAM/SCHEMATIC, 4.0 BCD - 5.0 BCD - SRC ①

SCALE: NONE
APP'D: **E**
DATE: 4/1/01

FIG. NO. **44732**